


VANGUARD PLATINUM

PART NO. 10331



PACKING LIST

- 1 - Vanguard Platinum Dust Collector(10330)
- 1 - Large Accumulator (VMC-A300)
- 1 - 2 1/2" x 3' Hose (VMC-1023A)
- 1 - 2 1/2" x 6' Hose (VMC-1023)
- 1 - Adapter for 1 1/2" Accessory (VMC-1036)
- 1 - Instructions

IMPORTANT SERVICE INFORMATION:
SAVE SHIPPING BOX AND FOAM FOR FUTURE SERVICE. SHIPPING WITHOUT PROPER FOAM MAY CAUSE DAMAGE TO UNIT

ASSEMBLY INSTRUCTIONS for VANIMAN VANGUARD SINGLE STATION

1. Remove the unit and other parts from the box and check against the packing list.
2. Mount the Accumulator according to the mounting instructions included with it or assemble the angle bracket to the dust collector as illustrated. Remove the two screws provided on the back of the unit and use them to fasten the angle bracket to the vacuum.
3. Connect the 2 1/2" hose from the unit to the top of the Accumulator. Gently rotate and push the hose end into the black foam gasket. Moistening the foam with water will ease assembly. The hose may be shortened to minimize suction loss by cutting the plastic with a sharp knife and the support wire with wire cutters. Longer hoses and adapters are available from your dealer. We recommend that you try to keep the total length of hose less than six feet between the unit and the dust



VANGUARD PLATINUM

PART NO. 10331

collection point. Longer hose will reduce suction. The hose cuffs thread off with a left hand thread.

- Two 4' hoses are provided to connect the tee assembly; the two beveled ends attach into tee (soften hose ends in warm tap water for easier assembly). Connect the tee assembly to the side of the Accumulator and route the hoses to the collection devices. Shorten hose as required to minimize suction loss.

SETTING UP THE AUTOPILOT

Introduction:

The **AutoPilot** allows you to control your dust collector from a micromotor or lathe. When you start your micromotor, the dust collector will start automatically. When you stop your micromotor, the dust collector will continue for a short period of time to allow for the residual dust to be cleared. **WARNING:**

The Autopilot will accommodate a micromotor, electric handpiece, or lathe that does not exceed **6 amps, 115VAC, total**

- Flip the black switch to "AUTOMATIC", the dust collector should go off.
- Plug one micromotor into the receptacle on the top of the Platinum. Try the micromotor or trimmer and the dust collector should start automatically.

NSK Z500 Series Handpiece Users

From the NSK Z500 Users manual:

"Vacuum-coupled Mode

On some dental tables with vacuum dust collector, the motor may be used while being coupled with a dust collector. When such a dust collector is used, power consumption of the Z500 can be regulated so that the vacuum-coupled function can work. If you need coupling with a vacuum dust collector, select the mode as follows:

How to select the mode

While pressing Forward/Reverse Selector Switch (button), turn on the Power Switch, and the mode can be selected. A long beep indicates vacuum-coupled mode and 2 short beeps indicate non-coupled mode. Each time the switch selection is made, the mode changes between vacuum-coupled mode and non-coupled mode."

MAINTENANCE

- Filter Bag Replacement** - When a noticeable drop in suction occurs or the unit will shut down, it may be time to replace the filter bag. **DO NOT** attempt to clean out the filter bag. Replace with a new Vaniman filter bag. Change the filter bag by unscrewing the two thumb screws located on the side panel, and remove the cover plate. The filter bag will now be exposed. Remove the used filter bag by sliding it off the inlet tube. The front of the cardboard reinforcement may need to be tilted downward slightly to remove bag easily. Once removed, check the inside of the filter bag compartment. If dust is present please clean out the filter compartment. Cause for residual dust may be that the filter bag was improperly installed. Vacuum out any dust before putting in a new bag; this will increase the life of the unit. Filter bag order number is **VMC-A400-5**, which can be ordered through your supplier.



VANGUARD PLATINUM

PART NO. 10331

2. **Installing a New Filter Bag** - slip the cardboard reinforcement, with rubber seal, over the inlet tube. You may need to tilt the front of the cardboard downward and slip the back edge up past the tube end, then rotate upward over the tube end. Carefully tuck the edges of the filter bag into the filter bag cavity. Replace the cover plate and gently tighten the thumb screws. Only gentle pressure need be used to make the gasket seal as the vacuum pressure will draw the cover tight.
3. **Circuit Breaker** - The unit is protected by a circuit breaker on the rear of the unit. In the unlikely event that there is an overload condition the breaker may trip. If this happens reset the breaker by pushing on the white button until it clicks into place.
4. **Motor protection** - the Vanguard motor is thermally protected against overload. If the unit becomes overheated, the thermal fuse will blow and must be replaced before the unit will operate again. A thermal Cutoff Kit can be ordered through the factory at 1-800-VANIMAN (826-4626) or through your supplier. **P/N 97013**

RECOMMENDED USAGE

1. Individual work station (2½" hose) or two station (1½" hoses) dust collection for cutting, grinding and polishing of metal, porcelain, plastic and stone.
2. The unit may be used alone or in conjunction with the Large Vaniman Pre-Filter Accumulator. The Accumulator will trap 90-95% of the dust in the collection trap, extending the life of the filter bag by up to 10 times.
3. The Vanguard Platinum 2x is **NOT RECOMMENDED** for use with aluminum oxide abrasive blasting. Such use will void the warranty. The fine abrasive particles will cause motor damage. However, Vaniman has a suction unit designed specifically for abrasive blasters; it is called the SandVac (**P/N 10211**). Contact your dealer for availability.

ACCESSORIES & REPLACEMENT PARTS

The following items are offered to enhance the usage of your quality Vaniman unit. These items can be order through your supplier using the following part numbers. Please feel free to contact Vaniman Mfg. Co. with questions regarding our products.

Odor Filter	P/N 96013
Post Filter	P/N 96014
HEPA Filter	P/N 96016
Filter Bag (5 Pack)	P/N VMC-A400-5
Filter Bag (3 Pack)	P/N VMC-A400-3
Remote Switch	P/N VMC-A450
Dual Remote Switch	P/N VMC-A455